


PRODUCT INFORMATION



QUIKRETE® is a registered trademark of QUIKRETE® International, Inc.
U.S. Trad. Off. Reg. Nos. 391,990; 767,396; 1,042,903
© 2005 Quikrete International, Inc., Atlanta, GA 30305



PRODUCT: 51020 Series

DESCRIPTION:

QUIKRETE® Multi-Surface Concrete Sealer

FEATURES:

This sealer is fortified with new, heavy-duty resin technology to provide maximum adhesion and protection on concrete surfaces. This solid color sealer protects and beautifies patios, driveways, pool decks and other exterior masonry surfaces. Do not apply this product over asphalt, damp or wet concrete or surfaces that have been treated with water repellent sealers.

COVERAGE/THINNING:

One gallon covers approximately 200-500 sq. ft. depending on surface texture. Do not thin.

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Dries to the touch in 2 hours, wait 24 hours for light use, 72 hours for automobile traffic.

SURFACE PREPARATION:

General:

All surfaces must be clean, dry and free of all loose, peeling paint or contaminants.

Bare Concrete: Allow 60 days minimum for new concrete to cure before sealing. Clean and etch new or bare concrete with BOND•LOK™ Cleaner, Degreaser & Etcher.

Follow all BOND•LOK label instructions.

Previously Painted/Stained Concrete:

Strip off all old coating and then follow bare concrete instructions.

02-51020 Series QUIKRETE Multi-Surface Concrete Sealer

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION:

Mix well before and during use. Intermix cans of the same color. Apply with a high quality polyester brush or 1/4" or 3/8" nap roller. Spread product evenly and finish with long, even strokes in the same direction. Two coats are recommended for most applications (wait 24 hours for second coat).

CLEAN UP:

Clean up with xylene.

STORAGE AND DISPOSAL:

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations. **Danger:** Rags, steel wool, sanding dust or waste soaked with this product may spontaneously catch fire if improperly discarded. Immediately after each use, place rags, steel wool, sanding dust or waste in a sealed, water-filled metal container.

**Product Information Hotline:
1-800-458-0047**

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.**

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

**This product contains less than
600 g/L VOC (5.0 lb./gal VOS)**

CAUTIONS:

CONTAINS ORGANIC SOLVENT AND CRYSTALLINE SILICA.

Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. May be harmful if absorbed through skin. Harmful if swallowed. Keep away from heat, sparks and flame. Vapors may cause flash fire. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent buildup of vapors by opening doors and windows to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. Close container after use. **Warning:** This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.** **SKIN CONTACT:** Wash thoroughly with soap and water.

IF INHALED: If you experience difficulty in breathing, leave the area to obtain fresh air. If breathing difficulty continues, **get medical attention immediately.**

IF SWALLOWED: Do not induce vomiting. **Get medical attention immediately.**

Delayed effect from long-term exposure: Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We assume no obligation or liability for use of this information. **UNLESS WE AGREE OTHERWISE IN WRITING, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIM ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. WE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.