


PRODUCT INFORMATION



QUIKRETE® is a registered trademark of QUIKRETE® International, Inc.
U.S. Trad. Off. Reg. Nos. 391,990; 767,396; 1,042,903
© 2005 Quikrete International, Inc., Atlanta, GA 30305



PRODUCT: 02-51092

DESCRIPTION:

QUIKRETE® Natural Look Waterproofer

FEATURES:

This product forms a long lasting, waterproofing seal on concrete, brick, masonry, exposed aggregate, natural stone and pavers. This sealer is fortified with new, heavy-duty resin technology to protect against the sun's powerful rays, water, gasoline and deicing salts. This protective sealer allows the natural look of the surface to come through. Do not use below grade.

SURFACE PREPARATION:

General:

All surfaces must be clean, dry and free of all loose, peeling paint or contaminants.

Bare Concrete:

Allow 60 days minimum for new concrete to cure before sealing.

Previously Sealed Surfaces:

Clean with an all-purpose cleaner (TSP or substitute). Previously sealed surfaces must be porous and able to accept additional sealer.

Test surface porosity before sealing:

Avoid using this product on non-porous, sealed surfaces. To test, place a few drops of water on surface. If water sinks in, the surface is porous enough to use this finish. If water remains on the surface, do not use.

02-51092 QUIKRETE Natural Look Waterproofer

COVERAGE/THINNING:

Covers approximately 75-150 sq. ft. (7-14 m²) per gallon, depending upon surface porosity. Do not thin.

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Dries in 1 hour.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead

APPLICATION:

Use a roller or low-pressure garden type sprayer. While the first coat is still wet, apply a second coat to maximize protection. Allow 5-10 minutes for final penetration, then use a clean, dry cloth to wipe off all excess which did not soak into the surface. **Do not pond or puddle this product.**

CLEAN UP:

Clean up with warm, soapy water.

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**Product Information Hotline:
1-800-458-0047**

CAUTIONS:

May cause eye and skin irritation. Avoid breathing vapors or spray mist. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.**

IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.**

IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.
EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

**This product contains less than
100 g/L VOC (0.8 lb./Gal VOS)**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We assume no obligation or liability for use of this information. **UNLESS WE AGREE OTHERWISE IN WRITING, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIM ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. WE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.