



PRODUCT INFORMATION



PRODUCT: 50085

DESCRIPTION:

QUIKRETE® Latex Masonry Waterproofer

FEATURES:

This product is fortified with new, heavy-duty resin technology to provide maximum adhesion while protecting your concrete surfaces with a watertight barrier guaranteed to stop water.

WHERE TO USE:

This advanced, low odor formula is ideal for basements. Use on properly prepared interior and exterior masonry walls and foundations, basements, cinder block, brick and poured concrete. Do not use on floors. If used outdoors, this product must be top coated with a top quality exterior latex house paint.

QUIKRETE® is a registered trademark of QUIKRETE® International, Inc.
U.S. Trad. Off. Reg. Nos. 391,990; 767,396; 1,042,903
© 2005 Quikrete International, Inc., Atlanta, GA 30305

SURFACE PREPARATION:

General: All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. Use a hydraulic cement patching compound on all cracks, holes and separations at joints and other areas where seepage occurs.

Bare Surfaces: If present, remove any white powdery residue with water and a scrub brush.

Previously Painted Surfaces: Use a tape test to ensure adequate adhesion. Press heavy-duty tape (i.e. duct tape) at various places on the painted surface. Pull the tape quickly from the surface. If the previous paint is removed by the tape, the paint must be fully removed before using this product.

REDUCE SEEPAGE:

Repair roof and gutter leaks, install downspout extensions and build up ground level next to the house. This will divert water away from the house, reduce hydrostatic water pressure on the walls and foundation and lower the potential for seepage.

50085 QUIKRETE Latex Masonry Waterproofer

TYPICAL PRODUCT PROPERTIES: (50085)

VEHICLE TYPE: Styrene Acrylic Resin
SOLIDS: 65% WT. 50% VOL.
VOC: 250 g/L max
WT/GAL: 12.5 lbs.
VISCOSITY: 105-115 KU
FLASHPOINT: N.A.
60° GLOSS: Flat

COVERAGE/THINNING:

Covers up to 60-100 sq. ft. (5.6-9.3 m²) per gallon on bare cinder block and cement surfaces and up to 200 sq. ft. (18.6 m²) on other surfaces, depending on porosity and texture. Do not thin.

FILM THICKNESS: 20 Mils Wet
10 Mils Dry

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Dries to the touch in 30-60 minutes.

APPLICATION:

Mix well before and during use. Apply 2 coats with a premium quality, long nap roller or very stiff brush. For first coat application only, moisten bare surfaces lightly with water. For the first coat, work the product into the surface using a brush or roller. Spread product evenly and finish with long, even strokes in one direction. Let dry 12 hours before applying second coat. Do not apply to walls that have active water seepage at the time of application.

CLEAN UP:

Cleans up easily with warm, soapy and water.

PACKAGING:

Gallon—4 Pack
3.5 Gallon—Each

STORAGE AND DISPOSAL:

Do not freeze. Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Product Information Hotline:
1-800-458-0047

TYPICAL ANALYSIS (50085 White)

CAS NO.	INGREDIENTS
7732-18-5	Water
NOT AVAIL.	Styrene Acrylic Resin
7631-86-9	Silica
13983-17-0	Wollastonite
14808-60-7	Silica
13463-67-7	Titanium Dioxide

CAUTIONS:

CONTAINS CRYSTALLINE SILICA

May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Avoid exposure to sanding dust by wearing an appropriate particulate respirator (NIOSH approved) during application, sanding and cleanup. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

Warning: This product contains a chemical known to the State of California to cause cancer.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water.

Get medical attention immediately.

Delayed effect from long-term exposure:

Cancer hazard. Crystalline silica can cause lung damage and cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

**This product contains less than
250 g/L VOC**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We assume no obligation or liability for use of this information. **UNLESS WE AGREE OTHERWISE IN WRITING, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIM ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. WE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.