



PRODUCT INFORMATION

QUIKRETE® is a registered trademark of QUIKRETE® International, Inc.
U.S. Trad. Off. Reg. Nos. 391,990; 767,396; 1,042,903
© 2005 Quikrete International, Inc., Atlanta, GA 30305



PRODUCT: 51060

DESCRIPTION:

QUIKRETE® Semi-Transparent Concrete Stain

FEATURES:

This product transforms ordinary concrete into an inviting space with a multi-colored appearance that looks like natural stone. The transparent, low gloss finish highlights natural variations and texture of concrete, brick, pavers, and unglazed tile and tone. The durable formula provides long lasting decorative color while protecting INTERIOR and EXTERIOR surfaces from water damage, household chemicals, and wear from foot and vehicle traffic. Ideal for use on floors, patios, pool decks, sidewalks, privacy walls and driveways. This product is not recommended for use on garage floors.

SURFACE PREPARATION:

General: All surfaces must be clean, dry and free of all loose, peeling paint or contaminants. Do not apply over surface treated with water repellent sealers.

Bare Concrete: Allow 30 days minimum for new concrete to cure before painting. Clean and etch new or bare concrete with BOND•LOK™ Cleaner, Degreaser & Etcher. **Follow all BOND•LOK label instructions.**

Previously Painted/Stained Concrete:

Strip off all old coating and then follow bare concrete instructions.

51060 QUIKRETE Semi-Transparent Concrete Stain

TYPICAL PRODUCT PROPERTIES:

(Tintable Base 51060)

VEHICLE TYPE: Acrylic Resin
SOLIDS: Proprietary
VOC: 100 g/L max
WT/GAL: 8.6 lbs.
VISCOSITY: Less than 53 KU
FLASHPOINT: N. A.
60° GLOSS: N. A.

COVERAGE/THINNING:

One gallon covers approximately 200-400 sq. ft (18.6 m² - 37.2 m²) depending on surface texture. Do not thin.

FILM THICKNESS: N. A. Penetrating Finish

DRY TIMES:

Apply only when surface and air temperatures are 50-90°F (10-32°C). Avoid application in direct sunlight or onto hot concrete surfaces. Dries to touch in 2 hours, ready for light use or for application of durable topcoats in 24 hours.

APPLICATION:

Mix well before and during use. Intermix cans of the same color. Wet concrete thoroughly with water. Apply stain in small sections (4' x 4') working quickly to maintain a wet edge. Apply with a pump sprayer, set to a fine spray, in a circular motion. For a more uniform appearance, immediately back-roll wet areas with a 3/8" nap roller. Do not let stain "puddle" on surface. Allow to dry 4 hours before deciding if another coat is needed. A second coat will yield a darker, more uniform color. **TIP:** For a more varied appearance, choose a two-color effect. Spray a second color onto the first wet coat of stain in a random pattern but do not back-roll.

Optional Topcoat: Use QUIKRETE #51390, Wet Look High Gloss Sealer, to provide maximum protection from household chemicals, wear in high traffic areas, and hot tire pick-up.

CLEAN UP:

Clean up with warm, soapy water.

PACKAGING:

Gallon—4 Pack

STORAGE AND DISPOSAL:

Do not freeze! Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, absorb with inert material such as sand or kitty litter. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Product Information Hotline:

1-800-458-0047

TYPICAL ANALYSIS (51060 Tintable Base)

CAS NO.	INGREDIENTS
7732-18-5	Water
Not Avail.	Acrylic Emulsion
Not Avail.	Proprietary Additive
37244-96-5	Nepheline Syenite
107-21-1	Ethylene Glycol

CAUTIONS:

May cause eye and skin irritation. Avoid breathing vapors or spray mist. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

FIRST AID:

EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** **IF INHALED:** If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** **IF SWALLOWED:** Drink 2 glasses of water. **Get medical attention immediately.**

**DO NOT TAKE INTERNALLY.
KEEP OUT OF REACH OF CHILDREN.
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

EMERGENCY MEDICAL TELEPHONE:

1-888-345-5732

**This product contains less than
100 g/L VOC**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We assume no obligation or liability for use of this information. **UNLESS WE AGREE OTHERWISE IN WRITING, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIM ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. WE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.