



## PRODUCT INFORMATION

QUIKRETE® is a registered trademark of QUIKRETE® International, Inc.  
U.S. Trad. Off. Reg. Nos. 391,990; 767,396; 1,042,903  
© 2005 Quikrete International, Inc., Atlanta, GA 30305



### PRODUCT: 96

### DESCRIPTION:

QUIKRETE® BOND•LOK™ Concrete Cleaner, Degreaser & Etcher

**Read directions and cautions thoroughly before using this product.**

### FEATURES:

This product prepares concrete for maximum durability and adhesion in one easy step. BOND•LOK degreases the surface, cleans away tough stains and oil spots, and etches concrete prior to painting or sealing.

### SURFACE PREPARATION:

Surface must be free of loose dirt, dust, leaves, dried paint or other debris. Use a stiff bristle broom to sweep floor. Clean out cracks and corners where dirt and other debris may be embedded or hard to reach. Tip: Use a leaf blower after sweeping to blow any excess dust or dirt off surface. Wet the surface down completely with a garden hose.

### HOW TO USE:

Wear rubber boots, rubber gloves and eye protection at all times while using this product. Protect plants and landscaping from direct contact and run-off. Transfer into a plastic watering can. **Do not use a metal watering can.** Inspect floor for grease and oil stains. Spot apply BOND•LOK directly to these areas and scrub thoroughly with a stiff brush. Rinse with water. Difficult areas may require a second application and scrubbing. Divide the surface into 10' X 10' sections. Pre-wet surface using a garden hose, avoid puddles.

**96 QUIKRETE BOND•LOK Concrete Cleaner, Degreaser & Etcher**

---

### TYPICAL PRODUCT PROPERTIES: (96)

PRODUCT TYPE: Organic Acid Salt solution  
SOLIDS: 19% WT. 14% VOL.  
VOC: 250 g/L max  
WT/GAL: 8.8 lbs.  
pH: 1.0 max  
FLASHPOINT: N.A.

### COVERAGE/THINNING:

Ready to use on garage floors. One gallon of BOND•LOK (as supplied) covers about 250 sq. ft. (1 car garage). For other areas such as patios, driveways, sidewalks, etc., mix BOND•LOK into one gallon of water and stir for 1 minute. This 2-gallon mixture will cover 500 sq. ft.

**APPLICATION:**

To apply BOND•LOK, sweep watering can back and forth as you pour to ensure complete coverage. Using a stiff bristle brush spread BOND•LOK over section completely. It should begin to fizz or bubble, this is normal. Note: If BOND•LOK is not fizzing, it is not working. The concrete may have been previously sealed, preventing the BOND•LOK from working. The sealers must be totally removed before reapplying BOND•LOK. Use the brush to scrub the solution into the surface in 2 directions, perpendicular to each other. Brush thoroughly in short, firm motions over stains and spots. When finished with one section, spray with water and wash away residue. Pre-wet the next 10' X 10' section and repeat steps. When finished, re-rinse completely with garden hose, washing away loosened material and cleaner residue. Keep rinsing until water runs clean. All loosened powders must be removed or they will interfere with coating adhesion. **Allow surface to dry completely, at least 4 hours or overnight, before applying any coating.**

**CLEAN UP:**

Rinse all tools, material and personal protection with water before storing.

**PACKAGING:**

Gallons—4 Pack

**STORAGE AND DISPOSAL:**

Keep container closed when not in use. Do not transfer contents to other containers for storage or disposal. In case of spillage, rinse with large amounts of clean water. Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

**Product Information Hotline:**

**1-800-458-0047**

**TYPICAL ANALYSIS (96)**

<b>CAS No.</b>	<b>Ingredients</b>
7732-18-5	Water
Not Avail.	Organic Acid Salt
34590-94-8	Dipropylene Glycol Methyl Ether
5131-66-8	Propylene Glycol Mono Butyl Ether

**CAUTIONS: CONTAINS ORGANIC ACID SALT AND ORGANIC SOLVENT.**

Harmful or fatal if swallowed. Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Do not breathe vapors. **Use only with adequate ventilation.** Prevent the buildup of vapors by opening all windows and doors to achieve cross-ventilation. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Contains ingredients, which may cause liver damage based on animal data. Do not get in eyes, on skin or clothing. Causes eye burns and skin irritation. Wash thoroughly after handling. Close container after each use.

**FIRST AID:**

**EYE CONTACT:** Flush immediately with plenty of water for at least 15 minutes and **get medical attention immediately.** **SKIN CONTACT:**

Wash thoroughly with soap and water.

**IF INHALED:** If you experience difficulty in breathing, leave the area to obtain fresh air.

If breathing difficulty continues, **get medical attention immediately.** **IF SWALLOWED:** Do not induce vomiting. **Get medical attention immediately.**

**Delayed effect from long-term exposure:**

Reports of commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.  
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.**

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**This product contains less than  
250 g/L VOC**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. We assume no obligation or liability for use of this information. **UNLESS WE AGREE OTHERWISE IN WRITING, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIM ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. WE WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option.